

AIR-62 PASSIVE INSTALLATION **SPEAKER**

AIR series is a comprehensive range of installation-dedicated speakers, backed-up with various mounting hardware options, including weatherproofing capability.

AIR-62 is the most compact speaker fitted with 6" cone transducer and 1" HF driver, and available with wide selection for mounting brackets. Special enclosure design conveniently fits into interior designs, providing for least visual footprint.







Main features:

- 150 W nominal power
 6" woofer with 1,75" voice coil
 1" HF driver with 1" voice coil
 124 dB Max SPL

| Frequency Response (-10dB) | 90 - 18000 Hz |
|---|--------------------------------------|
| Max SPL ¹ | 124 dB |
| Sensitivity (1W/1m) | 93 dB |
| LF Driver | 6", 1,75" VC |
| HF Driver | 1", 1" VC |
| Nominal Coverage Angle (Horizontal × Vertical) | 80 x 60 deg |
| Impedance | 8 / 16 Ohm |
| Nominal power ² | 150 W |
| Connectors | Barrier strip |
| Dimensions (W×H×D) | 278x318x200 mm |
| Net weight | 6 kg |
| Shipping weight | 7 kg |
| Mounting | VESA 75x75 3x M10 Mounting points |
| Enclosure material | Plywood; wear-resistant paint |
| Grill | Steel grill, polymer protective net |
| | |

- ¹ peak value, calculated according to AES 2 2012
- ² based on transducer power measured according to AES 2 2012

With dedication to constant improvement of the products, manufacturer may change the listed specifications without prior notice